Tango XXL PM Checklist

Tango XL Serial	Number:	

1. General condition of the chair

Date.	:						

Month	12	24	36	48	60	72	84	96	108	120
	C	C	C	C	Α	C	C	C	C	Α

Required tools

Touch- up pen Sikkens A77A2

- Visually check if the log, the instructioncart and the user manual are available. When it's not available, report this by the user.
- Visually check if all stickers are present and legible. Can you read the serial number yet? _____
- The CE Sticker should be present and clearly legible. This also applies to the sticker with inspection date.
- Visually check all painted parts for damage and corossion. Touch up if necessary.
- Check PUR parts for severe discolouration (Brown in particular) and damage.
- Are all the screws present and securely fitted? Also that of the guide?

Present:

Screws Present Y	' N	Screws replaced?	Y	N

- Foot supports (not a failure item) **Present :Y_____ N____**

For reasons of hygiene, it is strongly recommended to replace the seat and back once every 5 years.

2. Wheels

Month	12	24	36	48	60	72	84	96	108	120
	C	C	C	C	C	C	C	C	C	C

Required tools

Allen key 8mm



Figure 1 Wheel



Figure 2 wheel exploded

- Check the attachment of the wheel (Tolerance) ————
- Check freewheel function + brakes. _____
- Do all four the wheels touch the floor on a flat surface? If not, check the chair right course. ______
- Brake lip intact? ———
- Check the tread. _____

Replace the wheels if they are damaged or worn.

Wheels Replaced? Y____ N____

3. Arm rests

Month	12	24	36	48	60	72	84	96	108	120
	C	٧	C	٧	C	٧	C	٧	C	٧

Required tools

Allen key 6mm

- Inspect its functioning, and check for any damage, corrosion. —
- Check its room for motion, measured at the front point (replace if it is more than 4 cm.) .
- Always treat corossion.
- Are the arm supports evenly positioned? γ _____
- Is the secure bolt present? Y_____N_ REPLACE IF MISSING



Figure 3 Armrest

Replace bolts once every 2 years.

Look for an exploded view on www.lopital.nl

4. Foot support

1	Month	12	24	36	48	60	72	84	96	108	120
		C	C	C	C	C	С	I (С	C	C

Required tools

Allan key 4mm

- Check for any damage. —
- Fold up foot plates (should be stiff and stay upright). (They should remain in the folded position, without falling back automatically).
- Are the foot plates evenly fitted and slanting upwards a little towards the middle? —————



Figure 4 Foot support

Date/Time PM Completed
Tango XL Serial Number:
Secure Bolt Replacement Due Date
Tech Signature